

AquFlow

S900 PERFORMANCE TABLE

Model No.	Capacity GPH (LPH)	Pressure PSIG (bars)	Speed (SPM)	Plunger Diameter	Connection (NPT)
DM3T 1929-OX013	0.14 (0.53)	3,000 (200)	29	3/16"	1/4"
DM3T 1958-OX013	0.28 (1.06)	3,000 (200)	58	3/16"	1/4"
DM3T 1997-OX013	0.47 (1.78)	3,000 (200)	97	3/16"	1/4"
DM3T 1912-OX013	0.56 (2.12)	3,000 (200)	117	3/16"	1/4"
DM3T 1914-OX013	0.67 (2.54)	3,000 (200)	140	3/16"	1/4"
DM3T 1917-OX013	0.82 (3.10)	3,000 (200)	170	3/16"	1/4"
DM3T 2529-OX013	0.24 (0.91)	3,000 (200)	29	1/4"	1/4"
DM3T 2558-OX013	0.49 (1.85)	3,000 (200)	58	1/4"	1/4"
DM3T 2597-OX013	0.82 (3.10)	3,000 (200)	97	1/4"	1/4"
DM3T 2512-OX013	1.00 (3.79)	3,000 (200)	117	1/4"	1/4"
DM3T 2514-OX013	1.19 (4.50)	3,000 (200)	140	1/4"	1/4"
DM3T 2517-OX013	1.44 (5.45)	3,000 (200)	170	1/4"	1/4"
DM3T 3829-OX013	0.55 (2.08)	3,000 (200)	29	3/8"	1/4"
DM3T 3858-OX013	1.11 (4.20)	3,000 (200)	58	3/8"	1/4"
DM3T 3897-OX013	1.86 (7.04)	3,000 (200)	97	3/8"	1/4"
DM3T 3812-OX013	2.24 (8.48)	3,000 (200)	117	3/8"	1/4"
DM3T 3814-OX013	2.69 (10.18)	3,000 (200)	140	3/8"	1/4"
DM3T 3817-OX013	3.25 (12.30)	3,000 (200)	170	3/8"	1/4"

