



Pump Model Number	Capacity GPH (LPH)	Pressure psi	Speed SPM	Plunger Diameter	Connection (Metallic - NPT)
CNIT 0844-0X018	60.2 (91.27)	700 (48)	44	1"	1/2"
CNIT 0858-0X018	120.7 (120.3)	700 (48)	58	1"	1/2"
CNIT 0888-0X018	181.7 (182.49)	700 (48)	88	1"	1/2"
CNIT 0812-0X018	242.3 (242.64)	700 (48)	117	1"	1/2"
CNIT 0814-0X018	287.7 (290.34)	700 (48)	140	1"	1/2"
CNIT 1044-0X018	94.6 (143.39)	405 (28)	44	1-1/4"	1/2"
CNIT 1058-0X018	189.3 (189.04)	405 (28)	58	1-1/4"	1/2"
CNIT 1088-0X018	286.5 (286.82)	405 (28)	88	1-1/4"	1/2"
CNIT 1012-0X018	378.5 (381.34)	405 (28)	117	1-1/4"	1/2"
CNIT 1014-0X018	454.2 (456.29)	405 (28)	140	1-1/4"	1/2"
CNIT 1244-0X018	135.9 (205.81)	265 (18)	44	1-1/2"	1/2"
CNIT 1258-0X018	271.8 (271.3)	265 (18)	58	1-1/2"	1/2"
CNIT 1288-0X018	412.6 (411.63)	265 (18)	88	1-1/2"	1/2"
CNIT 1212-0X018	548.9 (547.26)	265 (18)	117	1-1/2"	1/2"
CNIT 1214-0x01A	645.9 (654.84)	265 (18)	140	1-1/2"	1-1/2"
CNIT 1444-0X018	185.1 (280.57)	180 (12)	44	1-3/4"	1/2"
CNIT 1458-0X018	370.2 (369.87)	180 (12)	58	1-3/4"	1/2"
CNIT 1488-0X018	560.2 (561.15)	180 (12)	88	1-3/4"	1/2"
CNIT 1412-0x01A	745.7 (746.1)	180 (12)	117	1-3/4"	1-1/2"
CNIT 1414-0x01A	893.4 (892.75)	180 (12)	140	1-3/4"	1-1/2"
CNIT 1644-0X018	241.9 (366.39)	130 (9)	44	2"	1/2"
CNIT 1658-0X018	484.5 (482.98)	130 (9)	58	2"	1/2"
CNIT 1688-0X01A	724.4 (732.78)	130 (9)	88	2"	1/2"
CNIT 1612-0X01B	976.6 (974.25)	130 (9)	117	2"	1-1/2"
CNIT 1614-0X01B	1165.9 (1165.79)	130 (9)	140	2"	1-1/2"
CNIT 1844-0X018	305.9 (463.41)	95 (7)	44	2-1/4"	1/2"
CNIT 1858-0X018	609.5 (610.89)	95 (7)	58	2-1/4"	1/2"
CNIT 1888-0X01A	927.4 (926.86)	95 (7)	88	2-1/4"	1-1/2"
CNIT 1812-0X01B	1234 (1232.3)	95 (7)	117	2-1/4"	1-1/2"
CNIT 1814-0X01C	1476.3 (1474.53)	95 (7)	140	2-1/4"	1-1/2"
CNIT 2044-0X018	378.5 (551.16)	75 (5)	44	2-1/2"	1/2"
CNIT 2058-0X01A	757.1 (726.53)	75 (5)	58	2-1/2"	1-1/2"
CNIT 2088-0X01B	1135.6 (1102.35)	75 (5)	88	2-1/2"	1-1/2"
CNIT 2012-0X01C	1514.2 (1465.6)	75 (5)	117	2-1/2"	1-1/2"
CNIT 2014-0X01C	1824.6 (1753.71)	75 (5)	140	2-1/2"	1-1/2"